

# Uniden® Link 4G

## Cradle Style Cellular Signal Booster

SKU: 2040CPAL

Everyone deserves great cellular signal



### UP TO 50X MORE SIGNAL

Enjoy crystal clear voice calls, and lightning fast data speeds



### MAGNET MOUNT

Secure any cellular device to the cradle with the built in extra strong magnet mount



### HIGH SPEED CHARGING PORT

USB-A 5V - 2.1Amp Output



### ALL NETWORKS

Works with all cellular operators 2G, 3G & 4G/LTE networks



### 2 YEAR WARRANTY

We stand behind our quality with a two year manufacturer warranty



### EASY INSTALLATION

Simple Plug & Play installation  
Everything you need is in the box!

## WORKS ON ALL CELLULAR OPERATORS NETWORKS



## WHATS IN THE BOX



Cradle Booster



Outdoor Antenna



Mounting Base with Suction Cup



Magnet Mount Metal Plates with Adhesive



Power Cable - 12 V

## HOW IT WORKS

### CRADLE BOOSTER

Boosts the cellular voice and data signals between the cradle and your phone, giving you a bigger and better coverage area

### LIGHTER PLUG POWER CABLE

Easily power your device with a lighter plug power cable that includes 2 extra USB charging ports



### OUTDOOR ANTENNA

Receives and sends cellular voice and data signals between the operator's tower and the signal booster



# Uniden® Link 4G

## BOOSTER TECHNICAL SPECIFICATIONS

RF Specification		Uplink	Downlink
Frequency Range	700 MHz Lower A+B+C	698 ~ 716 MHz	728 ~ 746 MHz
	700 MHz Upper C	776 ~ 787 MHz	746 ~ 757 MHz
	Cellular	824 ~ 849 MHz	869 ~ 894 MHz
	PCS	1850 ~ 1910 MHz	1930 ~ 1990 MHz
	AWS	1710 ~ 1755 MHz	2110 ~ 2155 MHz
Band width	Lower A+B+C Block / Upper C Block	18 MHz / 11 MHz	
	CDMA / PCS / AWS	25 MHz / 60 MHz / 45 MHz	
Max. Gain	700 MHz Lower A+B+C	15 ~ 20 dB	
	700 MHz Upper C	15 ~ 20 dB	
	Cellular	15 ~ 20 dB	
	PCS	15 ~ 20 dB	
	AWS	15 ~ 20 dB	
Max. Output Power		17~24dBm	-25~-30dBm
Inter-modulation		≤-19 dBm	≤-19 dBm
Spurious Emission		≤-13 dBm	≤-13 dBm
Electrical Parameter			
Power Supply	Input DC 6~13V, Output DC 5V / 2A		
Input & Output Impedance	50 ohm		
Mechanical Parameter			
I / O Port	SMB-Female		
Dimensions	135 * 65 * 26.5 mm		
Weight	≤ 0.5 Kg		
Environment Parameter			
Operating Temperature	-10 °C ~ +55 °C		
Relative Humidity	5 % - 95 %		
Environment Conditions	IP40		